




Sensor Lag Correction for Mobile Air Temperature Measurements in an Urban Microclimate Context



Kathrin Häb¹, Benjamin L. Ruddell², Ariane Middel³

¹Department of Computer Science, University of Kaiserslautern, PO Box 3049, 67653 Kaiserslautern, Germany

²The Polytechnic School, Arizona State University Polytechnic, 7231 E. Sonoran Arroyo Mall, Mesa AZ 85212

³Julie Ann Wrigley Global Institute of Sustainability, Arizona State University, PO Box 878009, Tempe AZ 85287-8009

Introduction

During mobile transect measurements, it is imperative to relate the measured values to sensor surroundings, which vary quickly in urban areas.

- **Problem:** Some sensors adapt slowly to the atmospheric conditions within the traversed microenvironments
- **Measure for the inertia of a sensor:** The *time constant* τ_{63} - the time [s] that a sensor needs to adapt to 63 % of an impulse change
- **The dynamical error:** Larger time constants *smooth* the recorded air temperature curve because local maxima and minima cannot be resolved [2, 3].

Research question and contribution

- How can measurements with a relatively slow sensor be corrected...
... in order to estimate high-resolution air temperature observations in an urban microclimate environment?
- Studies on sensor lag correction have been carried out in the context of radiosonde or airborne temperature measurements (e.g., [4, 5]), or in a micrometeorological context outside of urban areas (e.g., [2, 3])
- Studies on sensor lag correction in an urban setting are rare.

Instrumentation: The quest for ground truth




Fig. 1: The measurement platform. All sensors are mounted on a pole, which is attached to the front side of a golf cart. Data logger: Campbell Scientific CR1000.

	Fine-Wire Thermocouple (FWT)	Platinum Resistance Temperature Detector (RTD)
Model	Campbell Scientific Fw3, diameter: 0.0762 mm	Campbell Scientific HC253 (air temperature and rel. humidity probe)
Mounting height	1 m and 2 m	1 m and 2 m
Material	Chromel-Constantan	Platinum (resistance at 0°C = 100 Ω)
Accuracy	± 0.1 °C (at 23 °C)	± 0.1 °C (between 0 °C and 40 °C)
Time constant τ_{63}	0.6 s in still air (typical value, see [7])	172.7 s in still air (stdv = 0.08 s); 46.2 s for wind speeds > 3.2 m/s (stdv = 3.7 s)
Sampling frequency	1 Hz	1 Hz

- The time constant of the Pt100 RTD was determined experimentally.
- Air temperature time series were time-detrended individually.
- Since the time constant of the applied FWTs is very low, their observations can be used as a ground truth for the evaluation of algorithmic parameter choices.

Study site and transect runs




Fig. 2: The study site in Power Ranch, Gilbert, Arizona. The sample transect runs are plotted on top of a high-resolution land-use map [1].

Methodology

- **Basic assumption:** The measured temperature is the true temperature, convoluted with the time-derivative of the impulse-response function [2, 3, 4, 6].
- **Solution: Deconvolution!** Deconvolution procedures are described in [2, 3, 4, 6]. We base our approach mainly on [2], while optimizing the choice for two algorithmic parameters.

Correction algorithm Computational details Parameter choice




Fig. 3: Finding the optimal parameter choice for the correction algorithm by computing the root mean square error (RMSE), the mean absolute error (MAE), the maximal absolute error (Ae_{max}), and the index of agreement (d , as described in [5]) between corrected PRT data and the data from the fast FWT sensor.




Fig. 4: Results of the parameter optimization experiment, averaged over all available data sets.

Correction results





Fig. 5: Correction results when applying the algorithm as outlined above. The scatterplots show the improvement of the RMSE between PRT and FWT data after applying the correction. The time series below illustrate a best and a worst case scenario. FWT data was smoothed dependent on the minimal physical microclimate scale and platform velocity.

Conclusion and future work

- Applying the determined sensor lag correction procedure improves the agreement between PRT data (slow sensor) and FWT data (fast sensor) in all investigated settings.
- The results need to be verified for data sets representing different settings, e.g. in terms of sensor setup (other time constants) or season (winter / spring).

References

- [1] 4 Band NAIP Land Classification of Central Arizona: CAP LTER, by the Environmental Remote Sensing and Geoinformatics Lab, ASU, 2012.
- [2] C. Achberger, L. Barring: Correction of surface air temperature measurements from a mobile platform. *Agricultural and Forest Meteorology* 98 - 99: 227 - 238, 1999.
- [3] J.-C. Mayer, K. Hens, U. Rummel, F. X. Meixner, T. Foken: Moving measurement platforms - specific challenges and corrections. *Meteorologische Zeitschrift* 18 (5): 477 - 488, 2009.
- [4] G. W. Inverarity: Correcting airborne temperature data for lags introduced by instruments with two-time-constant responses. *Journal of Atmospheric and Oceanic Technology* 17 (2): 176 - 184, 2000.
- [5] C. J. Willmott: Some comments on the evaluation of model performance. *Bulletin of the American Meteorological Society* 63 (11): 1309 - 1313, 1982.
- [6] J. McCarthy, A method for correcting airborne temperature data for sensor response time. *Journal of Applied Meteorology* 12 (1): 211 - 214, 1973.
- [7] Omega Engineering, Inc.: Unsheathed fine gage microtemp thermocouples J, K, T, E, R & S. Online, last accessed: 08/11/2014. URL: http://www.omega.com/pptst/IRCO_CHAL_P13R_P10R.html

Acknowledgements

The authors wish to thank the Arizona State University Environmental Remote Sensing and Geoinformatics Lab (ERSG) for providing the NAIP data set (additional support was furnished by the Gilbert F. White Environment and Society endowment. Source data: National Agriculture Imagery Program (NAIP), <http://www.fsa.usda.gov>). This work was supported in part by the NSF Grant SES-0951366, Decision Center for a Desert City II: Urban Climate Adaptation, NSF EaSM Program EF-1049251, the NSF LTER Program BCS-1026865, the Salt River Project grant to ASU, Alan and Sandra Ruffalo, and the Power Ranch Homeowners Association. Any opinions, findings, and conclusions or recommendations expressed in this material are those of the authors and do not necessarily reflect the views of the sponsoring agencies.